

Opal

self contained



Electronic controller



Front breathing



Removable refrigeration cassette



Stainless steel worktop



10 Amp power

Opal cabinets are designed to perform in the harshest environments that kitchens can dish up. Through superior design and technology the Opal Front Breathing range doesn't miss a beat. Whether the cabinet has a blown air well or drawers it is the pinnacle of refrigerated cabinets.







Advantages










- 43°C ambient rating for hard working environments (32°C for LO4U)
- CoolSmart electronic controller for energy efficiency and even temperatures
- Easy clean covered internal liner
- Front breathing removable refrigeration cassette system for simple maintenance and easy servicing
- No need for external drain
- Face mounted hinges for plinth mounting
- Longer life anti corrosive evaporator coil coating
- Threaded castors allow simple leg changeover if required
- Intelligent ducted airflow distribution for greater even temperatures
- Two sets of non tilt adjustable pan slides per door—1/1 Gn sized shelves included
- Peace of mind auto defrost
- Designed and built to international quality standards for reliability and performance—HACCP compliant
- Interchangeable 1/1 Gastronorm racking system for total flexibility
- Optional long life heavy duty drawer systems with two and three drawer modules in both refrigerator and freezer
- Optional blown air well system (on refrigerator only) with directional air flow above and below the pan gives consistent temperatures
- Blown air well models supplied with one shelf per door as standard

Foodservice counters

**BA MODEL
TOP VIEW**



**STANDARD MODEL
TOP VIEW**



MODEL		1 DOOR	2 DOOR	3 DOOR	4 DOOR
H (Refrigerator +1°/+4°C)	FB (Front Breathing)	H01UFB	H02UFB	H03UFB	H04UFB
H (Refrigerator +1°/+4°C)	BA (Blown Airwell) Pans 100 mm deep Gn (included)	H01UFBBA 2 X 1/3	H02UFBBA 4 X 1/3	H03UFBBA 7 X 1/3	H04UFBBA 10 X 1/3
L (Freezer -18°/-22°C)	FB (Front Breathing)	L01UFB	L02UFB	L03UFB	L04UFB

SPECIFICATIONS

CAPACITY LITRES	190	350	510	670
DIMENSIONS - W X D X H (ON CASTORS) MM	955 W x 650 D x 845 H	1420 W x 650 D x 845 H	1885 W x 650 D x 845 H	2350 W x 650 D x 845 H
WEIGHT UNPACKED (KG)	100	130	160	190

STANDARD INCLUSIONS ***

DOOR TYPE

Standard: **SD** (Solid Door) Optional: **DR** (Drawer), **GD** (Glass Door), **PT** (Pass-Through)

FINISH (INTERIOR AND EXTERIOR EXCLUDING REAR AND UNDER)

SS (Stainless Steel)

SHELVES/DOOR

2/1(BA)

2/1(BA)

2/1(BA)

2/1(BA)

ELECTRICAL

POWER SUPPLY	10 amp	10 amp	10 amp	10 amp	
FRIDGE MODELS	RUNNING AMPS	2.0	2.8	3.1	3.7
BLOWN AIRWELL MODELS	RUNNING AMPS	2.9	3.9	4.6	5.0
FREEZER MODELS	RUNNING AMPS	3.0	4.5	4.7	5.3

GAS TYPE

REFRIGERANT	FRIDGE MODELS	R134a	R134a	R134a	R134a
	FREEZER MODELS	R404a	R404a	R404a	R404a