HTG15

| CATEGORY | TOPAZ RANGE | |
|----------|--------------------|--|
| RANGE | Topaz Cake Display | |
| UNIT | REFRIGERATOR | |
| TYPE | SELF CONTAINED | |
| SHELVES | 3 | |





Aluminium door track with cold stop strip Top and front glass are mitre joined. I piece with heated film. Upstand offers Heated door frame, 36V rear glass protection - Sliding door: 2-layer Low-E glass # 670 300 -# 1 213 1 21 - 20 1200 22 00 品 4 L 30 - 1500 -30 -680 Removable magnetic cover Dixell Controller -Removable front panel, fixed with screws Front View Section View Side View Back View

SPECIFICATIONS

| SI LOII IOATIONS | |
|--|-------------------------------|
| TEMPERATURE (38°C / 65% HUMDITY ENVIRONMENT) | 2°C / 8°C |
| DIMENSIONS - W X D X H (ON CASTORS) MM | 1500 W x 680 D x 1200 H |
| WEIGHT UNPACKED (KG) | 300 |
| DOOR TYPE | SL (Sliding Rear Doors) |
| GLASS PANELS (EXCLUDING REAR DOORS) | HEATED |
| FINISH | SS (Stainless Steel exterior) |
| SHELVES (INCLUDING BASE) | 3 |
| ELECTRICAL | |
| POWER SUPPLY | 10 amp |
| POWER CABLE LENGTH (METRES) | 2 |
| RUNNING AMPS | 5.5 |
| GAS TYPE | |
| REFRIGERANT | R134a |
| | |